



BOOST SERIES

ALUMINUM CARGO

STANDARD FEATURES:

CHASSIS:

- ALL ALUMINUM TUBE PERIMETER FRAME
- 24" OC SIDE WALL CONSTRUCTION
- 24" OC ROOF BOWS
- 24" FLOOR CROSS MEMBERS
- 2000# TOP WIND JACK (ZINC COATED)
- 5' AND 6' WIDES = 18" WEDGE (SLANTED)
- 7' WIDES = 24" WEDGE (SLANTED)
- 2" A-FRAME COUPLER FOR SA (ZINC COATED)
- 2-5/16" A-FRAME COUPLER FOR TA (ZINC COATED)
- SPRING AXLES W/EASY LUBE HUBS & BRAKES ON TA35
- 7-WAY MOLDED PLUG
- 3/4" ADVANTECH FLOORING

EXTERIOR:

- .030 ALUMINUM SCREWLESS EXTERIOR
- RAMP DOOR SPRING ASSISTED W/ ZINC BAR LOCKS
- 32" RV STYLE SIDE DOOR W/RECESSED FLUSH LOCK
- PLASTIC FLOW THROUGH VENTS
- 3" TOP AND 1 1/2" BOTTOM TRIM
- 16" ATP STONE GUARD W/J RAIL TRIM (SLANTED)
- 1 PC ALUMINUM ROOF (BONDED)
- ST205/75D15 BIAS TIRES
- SILVER POWDER COATED WHEELS
- NO SIDE DOOR ON 5' WIDE
- LED TAIL AND CLEARANCE LIGHTS
- 1 YEAR LIMITED WARRANTY

INTERIOR:

- 3/8" PLYWOOD WALLS
- 1-12V INTERIOR LIGHT W/SWITCH
- 12V- WIRING HIDDEN NOT EXPOSED TO THE WEATHER
- 6' INTERIOR HEIGHT
- 6' WIDE 70" INTERIOR WIDTH
- 7' WIDE 81" INTERIOR WIDTH